

TECHNICAL PASSPORT OF THE PRODUCT

PE-RT RAFTEC pipe with oxygen barrier blue

1. Purpose and scope

Raftec «PE-RT» pipes - can be used in internal cold and hot water supply systems, low-temperature heating systems. The main purpose of the pipes is the device of built-in heating systems (warm floors, warm walls, heating of open areas) and intra-apartment water supply pipelines. The pipes can be used as technological pipelines for transporting liquids that are not aggressive to the pipe material. The pipes are connected using **Raftec** press fittings.

PE-RT pipe with an oxygen barrier - outer diameter 16 with a wall thickness of 2.0 mm. The copolymer for PE-RT is octene, not butene, as for ordinary polyethylene. The spatial adhesion of PE-RT appears not due to additional interatomic bonds, but due to the interweaving of the branches of the copolymer. The pipe has a coating on the outside of a protective anti-diffusion layer of EVOH (ethylene vinyl alcohol), which prevents the diffusion of oxygen by the coolant. Resistant to ultraviolet radiation, a very smooth inner surface, not subject to deposits and high-temperature resistance.

They are used in the "warm floor" system.



2. Technical specifications

№	Characteristic	Value	
1	Article	RPERT16200	RPERT16600
2	Outer diameter, mm	16	
3	Inner diameter, mm	12	
4	Wall thickness, mm	2.0	
5	Bay length, m	200	600
6	Weight of 1 mm pipe, g	98	
7	Volume of liquid in 1 m.p., l	0.103	
8	Operating temperature at a pressure of 10 bar, °C	0-70	
9	Operating temperature at a pressure of 6 bar, °C	0-90	
10	Maximum operating temperature, °C	80	
11	Maximum short-term permissible temperature, °C	90	
12	Nominal pressure PN, bar	10	
13	Coefficient of equivalent uniform-grained roughness, mm	0.007	
14	Thermal conductivity coefficient of walls, W / (m · K)	0.38	
15	Minimum manual bending radius	8 x d	
16	Coefficient of linear expansion, mm/m (°C)	1,8 x 10 ⁻⁴	

3. Operating class

Type Operation class	Outer diameter dn(mm)	P (bar)	T (°C)	Protection Evon	Type of pipe
Cold water transportation	16	10	20	+	PEX-a grey
	20	10	20	+	PEX-a grey
	25	10	20	+	PEX-a grey
	32	10	20	+	PEX-a grey
Hot water distribution systems (Operation class 1)	16	10	60	+	PEX-a grey
	20	10	60	+	PEX-a grey
	25	10	60	+	PEX-a grey
	32	10	60	+	PEX-a grey
Hot water distribution systems (Operation class 2)	16	10	70	+	PEX-a grey
	20	10	70	+	PEX-a grey
	25	10	70	+	PEX-a grey
	32	10	70	+	PEX-a grey
Low-temperature heating – underfloor heating system (Operation class 4)	16	10	50	+	PEX-a red, PE-RT PEX-a grey
High-temperature heating – radiator heating (Operation class 5)	16	10	80	+	PEX-a grey
	20	10	80	+	PEX-a grey
	25	10	80	+	PEX-a grey
	32	10	80	+	PEX-a grey

4. Installation and operating instructions

1. Installation must be performed by qualified and competent personnel.
2. Pipe installation must be carried out at an ambient temperature of at least 10 ° C using a tool specially designed for this purpose.
3. It is recommended to use Raftec press fittings and crimp fittings as pipe connectors. When working with these fittings, you should follow the instructions in the relevant technical data sheets.
4. Flattening and fractures of the pipeline during installation are not allowed. In case of a "knock", the damaged section of the pipe must be destroyed.
5. Pipe coils that have been stored or transported at temperatures below 0°C must be kept for 24 hours at a temperature not lower than 10°C before rolling.
6. The free ends of the pipes must be closed with plugs to prevent dirt and debris from entering the pipe.
7. To avoid straightening of the bent section of the pipe when heated (memory effect), the pipe should be secured with clamps or brackets at 10 cm intervals at the points of rotation.
8. The underfloor heating pipeline should be filled with concrete mortar or covered with a coating only after hydraulic tests for tightness have been carried out. The pipe should be under a pressure of 0.3 MPa when filled;
9. The minimum height of the solution above the surface of the pipe must be at least 3 cm.
10. Mechanical damage to the EVOH layer increases oxygen penetration into the pipeline.
11. The pipe should be protected from direct sunlight.
12. Do not allow ice to form inside the pipe to prevent damage.
13. For installation, we recommend using a specialized Raftec tool.
14. The pipe must be operated under the conditions specified in the tables in section No. 2 "Technical specifications".

5. Storage and transportation

1. During rail and road transportation, coils (packages) of pipes are allowed to be transported only in covered rolling stock.
2. To avoid damage to the pipes, they should be laid on a flat surface, without sharp protrusions and irregularities. Dropping pipes from vehicles is not allowed..
3. Pipes must be stored in accordance with conditions 5 (OZH4), section 10 of GOST 15150 in ventilated sheds or rooms.
4. Pipe coils may be stored in stacks no higher than 3 m. When stored, pipes must be protected from direct sunlight.
5. The pipe must be stored in the manufacturer's packaging under storage conditions 3 according to GOST 15150-69.
6. Pipe transportation must be carried out in accordance with requirements 5 of GOST 15150-69.

6. Utilization

Disposal of the product (melting, burial, resale) in accordance with the procedure established by the Law of Ukraine of 1992 No. 50, Art. 678, (as amended by No. 2556 - III (2556-14) of 21.06.2001, No. 48, Art. 252 "On Atmospheric Air Protection" (as amended by 14.07.2016), of 1998 No. 36-37, 242 "On Waste" (as amended by 09.04.2015), of 1991 No. 41, Art. 546 "On Environmental Protection" (as amended by 04.10.2016), as well as other norms, acts, rules, orders, etc.

7. Warranty obligations

1. The manufacturer guarantees that the products comply with safety requirements, provided that the consumer complies with the rules of use, transportation, storage, installation and operation.
2. The warranty covers all defects caused by the manufacturer's fault.
3. The warranty does not cover defects that occur in the following cases:
 - violation of passport regimes for transportation, storage, installation, operation and maintenance of the product;
 - improper transportation and loading and unloading operations;
 - the presence of traces of exposure to substances that are aggressive to the product materials;
 - the presence of damage caused by fire, natural disasters, force majeure circumstances;
 - the presence of damage caused by incorrect actions of the consumer;
 - the presence of traces of third-party interference in the design of the product.
4. The manufacturer reserves the right to make changes to the product design that do not affect the declared technical characteristics.

8. Warranty terms and conditions

1. Claims for the quality of the goods may be made during the warranty period.
2. Defective products during the warranty period are repaired or exchanged for new ones free of charge. The decision to replace or repair the product is made by the service center. The replaced product or its part obtained as a result of the repair becomes the property of the service center.
3. The costs associated with dismantling, installation and transportation of the defective product during the warranty period are not reimbursed to the Buyer.
4. In cases where the claim is unfounded, the costs of diagnostics and examination are paid by the Buyer.
5. Products are accepted for warranty repair (as well as when returned) fully equipped.

WARRANTY CARD № _____

Product name _____

Brand, article, size _____

Quantity _____

Name and address of the trading organization _____

Date of sale _____ Seller's signature _____

Stamp or seal

of the trading organization

I AGREE with the conditions:

BUYER _____

(signature)

The warranty period is seven years (eighty-four months) from the date of sale to the end consumer.

For warranty repair, complaints and claims regarding the quality of products, please contact the service center at the address: 08132, Kyiv region, Vyshneve, Kyivska st., building 6b.
Tel.: + 38(050)-315-16-33

When making claims regarding the quality of the goods, the buyer shall provide the following documents:

1. A statement in any form, indicating:
 - name of the organization, full name of the buyer, actual address and contact phone number;
 - name and address of the organization that performed the installation;
 - main system parameters;
 - short description of the defect;
2. Document proving the purchase of the product;
3. Hydraulic test certificate of the system in which the product was installed;
4. A completed warranty card issued on the manufacturer's website «raftec.eu».

Return or exchange mark: _____

Date _____ y. Signature: _____